



## Features

- Fundamental /3rd overtone solution.
- 3.3V / 2.5V operation voltage.
- LVDS output, output frequencies 25MHz to 200MHz.
- Excellent low phase noise and jitter.
- 3-state function available.
- Automatic mounting and reflow soldering.
- Applications: Ethernet, Server, SDH, SONET, PC, Mobile Telecommunications, etc.



## Electrical Specifications

Type	SMD 5032 LVDS Crystal Oscillator
Output Type	LVDS
Output Load	100 Ω
Oscillation Mode	Fundamental / 3rd Overtone
Supply voltage	2.5V, 3.3V
Frequency range	25MHz~200MHz
Overall Frequency Stability*	±50ppm, or specify
Operating Temperature Range	-20~+70°C, -40~+85°C, or specify
Storage Temperature Range	-55~+125°C
Voltage Vol (Typ.) / Voh (Typ.)	0.9V / 1.6V
Rise(Tr) / Fall(Tf) Time(20%~80%)	1ns Max.
Supply Current	80mA Max.
Symmetry	45~55%
Start-up Time	10ms Max.
Phase Jitter(12kHz~20MHz)	1ps Max.

\* Inclusive of frequency tolerance at 25°C, variation over temperature, supply voltage variation, aging and vibration.

## Ordering Information

KOL5032	025M	25	50	A	
Product Code	Frequency Range 25MHz	Supply Voltage 25=2.5V	Frequency Stability 50=±50ppm	Operating Temperature	
				A:-20~+70°C	D:-40~+125°C
				B:-10~+70°C	E:-10~+60°C
				C:-40~+85°C	F:-30~+70°C

## Dimension

Units:mm

