



DESCRIPTION

The ES2AW~ES2JW are available in SOD-123FL package

ORDERING INFORMATION

Package Type	Part Number
SOD-123FL	ES2AW
	ES2BW
	ES2CW
	ES2DW
	ES2EW
	ES2GW
	ES2JW
Note	SPQ: 3,000pcs/Reel
AiT provides all RoHS Compliant Products	

FEATURES

- Easy pick and place
- For surface mounted applications
- Low profile package
- Built-in strain relief
- Superfast recovery times for high efficiency
- Available in SOD-123FL package


MECHANICAL DATA

Case: SOD-123FL

Terminals: Solderable per MIL-STD-750,
Method 2026

Approx. Weight: 15mg / 0.00053oz

PIN DESCRIPTION





ABSOLUTE MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate current by 20%.

Parameter	Symbol	ES2AW	ES2BW	ES2CW	ES2DW	ES2EW	ES2GW	ES2JW	Unit
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	50	100	150	200	300	400	600	V
Maximum RMS Voltage	V_{RMS}	35	70	105	140	210	280	420	V
Maximum DC Blocking Voltage	V_{DC}	50	100	150	200	300	400	600	V
Maximum Average Forward Rectified Current at $T_L=100^\circ\text{C}$	$I_{F(AV)}$	2							A
Peak Forward Surge Current 8.3ms Single Half Sine Wave Superimposed on Rated Load (JEDEC Method)	I_{FSM}	50							A
Maximum Forward Voltage at 2A	V_F	1				1.25		1.68	V
Maximum DC Reverse Current at Rated DC Blocking Voltage	I_R					5	100		uA
Typical Junction Capacitance at $V_R=4V, f=1\text{MHz}$	C_J	25							pF
Maximum Reverse Recovery Time ^{NOTE1}	t_{rr}	35							ns
Typical Thermal Resistance ^{NOTE2}	$R_{\theta JA}$	90							°C/W
Operating and Storage Temperature Range	$T_J,$ T_{STG}	-55 ~150							°C


NOTE1: Measured with $I_F = 0.5\text{ A}$, $I_R = 1\text{ A}$, $I_{rr} = 0.25\text{ A}$

NOTE2: P.C.B. mounted with 2.0" X 2.0" (5 X 5 cm) copper pad areas.



TYPICAL CHARACTERISTICS

Figure. 1 Reverse Recovery Time Characteristic and Test Circuit Diagram



Note: 1. Rise Time = 7ns, max.
Input Impedance = 1megohm, 22pF.
2. Rise Time = 10ns, max.
Source Impedance = 50 ohms.




Figure. 2 Maximum Average Forward Current Rating




Figure. 3 Typical Reverse Characteristics






Figure. 4 Typical Forward Characteristics




Figure. 5 Typical Junction Capacitance





Figure. 6 Maximum Non-Repetitive Peak Forward Surge Current







PACKAGE INFORMATION

Dimension in SOD-123FL(Unit: mm)

Plastic surface mounted package; 2 leads



The recommended mounting pad size



UNIT		A	C	D	E	e	g	H _E	∠
mm	Max	1.1	0.20	2.9	1.9	1.1	0.9	3.8	7°
	Min	0.9	0.12	2.6	1.7	0.8	0.7	3.5	
mil	Max	43	7.9	114	75	43	35	150	
	Min	35	4.7	102	67	31	28	138	



IMPORTANT NOTICE

AiT Semiconductor Inc. (AiT) reserves the right to make changes to any its product, specifications, to discontinue any integrated circuit product or service without notice, and advises its customers to obtain the latest version of relevant information to verify, before placing orders, that the information being relied on is current.

AiT Semiconductor Inc.'s integrated circuit products are not designed, intended, authorized, or warranted to be suitable for use in life support applications, devices or systems or other critical applications. Use of AiT products in such applications is understood to be fully at the risk of the customer. As used herein may involve potential risks of death, personal injury, or severe property, or environmental damage. In order to minimize risks associated with the customer's applications, the customer should provide adequate design and operating safeguards.

AiT Semiconductor Inc. assumes to no liability to customer product design or application support. AiT warrants the performance of its products of the specifications applicable at the time of sale.